	Datasheet	No.	DS10-J003
		Initial Date	2014-05-28
OJ	OJ7S341	Written Team	R&D Dept.
			GH Zheng

### I Preview


PN	OJ7S341
Description	40G QSFP+LR4 4CWDM CH LCDDMI 0~70 °C

### II Contents

1. Features
2. Applications
3. Description
4. Absolute maximum Ratings
5. Operating Environment
6. Optical and Electrical Characteristics
7. Digital Diagnostic Memory Map
8. Pin Descriptions
9. Mechanical Dimensions
10. Model Ordering Information

### III Revision History

No.	Date	Items	Change Recording	Ver.	Rev.	Customer
1	2014-05-28	All	Initial registration	000	000	Standard
2						
3						
4						
5						
6						

 Communication Limited	Datasheet		DS10-J003 Final Rev.: 2014-05-28	
	Product	40G QSFP+ transceiver OJ serials	Ver.	000
	Part No.	OJ7S341	Rev.	000
			Page	2 / 8

### 1. Features:

- ◆ 4 CWDM lanes MUX/DEMUX design
- ◆ Transmission data rate up to 11.3Gbps per channel
- ◆ SMFLC duplex connector
- ◆ Hot Pluggable QSFP+ form factor
- ◆ Up to 10 km transmission
- ◆ Compatible with RoHS
- ◆ Single +3.3V power supply
- ◆ Real Time Digital Diagnostic Monitoring
- ◆ Operating case temperature: 0 to +70°C

### 2. Applications

- ◆ 40GBASE-LR4 Ethernet
- ◆ Switch, router and HBAs
- ◆ Data Center Interconnect
- ◆ Infiniband QDR
- ◆ 40G Campus Link

### 3. Description

The 40G QSFP+ LR4 transceivers are high performance, cost effective modules supporting data rate of 40Gbps and 10km transmission distance with SMF. The transceiver consists of three sections: 4 inputs channels (ch) of 10Gb/s electrical data to 4 CWDM optical signals, and multiplexes them into a single channel for 40Gb/s optical transmission; on the receiver side, the module optically de-multiplexes a 40Gb/s input into 4 CWDM channels signals, and converts them to 4 channel output electrical data; and MCU control unit. All modules satisfy class I laser safety requirements. The transceivers are compatible with 40GBASE-LR4 of IEEE802.3ba standard and SFF-8436 specification.

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL



Communication Limited

Datasheet

DS10-J003  
Final Rev.: 2014-05-28


Product: 40G QSFP+ transceiver  
OJ serials

Part No.: OJ7S341

Ver.: 000

Rev.: 000

Page: 3 / 8



Transceiver functional diagram

4. Absolute Maximum Ratings


Parameter	Symbol	Min	Max	Unit
Supply Voltage	Vcc	-0.5	4.5	V
Storage Temperature	Ts	-40	+85	°C
Operating Humidity	-	5	85	%

5. Operating Environment

Parameter	Symbol	Min	Typical	Max	Unit
Operating Case Temperature	Tc	0		+70	°C
Power Supply Voltage	Vcc	3.135	3.30	3.465	V
Power Dissipation	Pm			3.5	W
Data Rate			10.3125	11.3	Gbps

6. Optical and Electrical Characteristics


OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 Communication Limited	Datasheet		DS10-J003 Final Rev.: 2014-05-28	
	Product	40G QSFP+ transceiver OJ serials	Ver.	000
	Part No.	OJ7S341	Rev.	000
			Page	4 / 8

Parameter	Symbol	Min	Typical	Max	Unit	Notes
<b>Transmitter</b>						
Centre Wavelength	L0	1264.5	1271	1277.5	nm	
	L1	1284.5	1291	1297.5	nm	
	L2	1304.5	1311	1317.5	nm	
	L3	1324.5	1331	1337.5	nm	
-20dB Spectral Width	$\Delta\lambda$			1	nm	
Side-mode Suppression Ratio	SMSR	30	-		dB	
Total Average Launch Power	$P_T$			8.3	dBm	
Average launch power, each lane	$P_{out}$	-7		2.3	dBm	
Extinction Ratio	ER	3.5			dB	
Average launch power of OFF transmitter,each lane	$P_{off}$			-30	dBm	
Relative Intensity Noise	$R_{in}$			-128	dB/Hz	12dB reflection
Transmitter Reflectance	$R_T$			-12	dB	
Data Input Swing Differential	$V_{IN}$	190		700	mV	
Input Differential Impedance	$Z_{IN}$	90	100	110	$\Omega$	
<b>Receiver</b>						
Centre Wavelength	L0	1264.5	1271	1277.5	nm	
	L1	1284.5	1291	1297.5	nm	
	L2	1304.5	1311	1317.5	nm	
	L3	1324.5	1331	1337.5	nm	
Damage threshold	THd	3.3			dBm	
Average power at receiver input,each lane		-13.7		2.3	dBm	
LOS De-Assert	LOS <sub>D</sub>			-15	dBm	
LOS Assert	LOS <sub>A</sub>	-30			dBm	
LOS Hysteresis		0.5			dB	
Receive Electrical 3 dB upper Cutoff Frequency, each Lane	Fc			11.3	GHz	


## 7. Digital Diagnostic Memory Map

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-J003 Final Rev.: 2014-05-28	
	Product	40G QSFP+ transceiver OJ serials	Ver.	000
	Part No.	OJ7S341	Rev.	000
			Page	5 / 8

The transceivers provide serial ID memory contents and diagnostic information about the present operating conditions by the 2-wire serial interface (SCL, SDA).

The digital diagnostic memory map specific data field defines as following.



## 8. Pin Descriptions

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL



Communication Limited

Datasheet

DS10-J003  
Final Rev.: 2014-05-28

Product

40G QSFP+ transceiver  
OJ serials

Ver.

000

Part No.


OJ7S341

Rev.

000


Page

6 / 8



PIN	Logic	Symbol	Name/Description	Note
1		GND	Ground	1
2	CML-I	Tx2n	Transmitter Inverted Data Input	
3	CML-I	Tx2p	Transmitter Non-Inverted Data output	
4		GND	Ground	1
5	CML-I	Tx4n	Transmitter Inverted Data Input	
6	CML-I	Tx4p	Transmitter Non-Inverted Data output	
7		GND	Ground	1
8	LVTTL-I	ModSelL	Module Select	
9	LVTTL-I	ResetL	Module Reset	
10		VccRx	+ 3.3V Power Supply Receiver	2
11	LVC MOS-I/O	SCL	2-Wire Serial Interface Clock	
12	LVC MOS-I/O	SDA	2-Wire Serial Interface Data	
13		GND	Ground	
14	CML-O	Rx3p	Receiver Non-Inverted Data Output	
15	CML-O	Rx3n	Receiver Inverted Data Output	
16		GND	Ground	1

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-J003 Final Rev.: 2014-05-28	
	Product	40G QSFP+ transceiver OJ serials	Ver.	000
	Part No.	OJ7S341	Rev.	000
			Page	7 / 8

17	CML-O	Rx1p	Receiver Non-Inverted Data Output	
18	CML-O	Rx1n	Receiver Inverted Data Output	
19		GND	Ground	1
20		GND	Ground	1
21	CML-O	Rx2n	Receiver Inverted Data Output	
22	CML-O	Rx2p	Receiver Non-Inverted Data Output	
23		GND	Ground	1
24	CML-O	Rx4n	Receiver Inverted Data Output	1
25	CML-O	Rx4p	Receiver Non-Inverted Data Output	
26		GND	Ground	1
27	LVTTIL-O	ModPrsL	Module Present	
28	LVTTIL-O	IntL	Interrupt	
29		VccTx	+3.3 V Power Supply transmitter	2
30		Vcc1	+3.3 V Power Supply	2
31	LVTTIL-I	LPMode	Low Power Mode	
32		GND	Ground	1
33	CML-I	Tx3p	Transmitter Non-Inverted Data Input	
34	CML-I	Tx3n	Transmitter Inverted Data Output	
35		GND	Ground	1
36	CML-I	Tx1p	Transmitter Non-Inverted Data Input	
37	CML-I	Tx1n	Transmitter Inverted Data Output	
38		GND	Ground	1


Notes:


1. GND is the symbol for signal and supply (power) common for QSFP modules. All are common within the QSFP module and all module voltages are referenced to this potential unless otherwise noted. Connect these directly to the host board signal common ground plane.

2. VccRx, Vcc1 and VccTx are the receiver and transmitter power suppliers and shall be applied concurrently. Recommended host board power supply filtering is shown below. Vcc Rx, Vcc1 and Vcc Tx may be internally connected within the QSFP transceiver module in any combination. The connector pins are each rated for a maximum current of 500mA.

## 9. Mechanical Dimensions

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-J003 Final Rev.: 2014-05-28	
	Product	40G QSFP+ transceiver OJ serials	Ver.	000
	Part No.	OJ7S341	Rev.	000
			Page	8 / 8



#### 10. Module Ordering information

PN	Description
OJ7S341	40G QSFP+LR4 4CWDM CH LCDDMI 0~70 °C

OCRE COMMUNICATION LIMITED Web: ww.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL