



Datasheet

No.

DS10-E054

Initial Date

2017-07-21

OE

OEMCx41

Written Team

R&D Dept.

GH Zheng

I Preview


PN	OEMCx41
Description	25G SFP28 CWDM xxnm 10KMLC DDMI 0~70 °C

II Contents

1. Features
2. Applications
3. Description
4. Absolute maximum Ratings
5. Operating Environment
6. Optical and Electrical Characteristics
7. Timing and Electrical
8. Diagnostics
9. Pin Information
10. Digital Diagnostic Monitor Characteristics
11. Recommended Circuit
12. Mechanical Dimensions
13. Model Name Information

III Revision History

No.	Date	Items	Change Recording	Ver.	Rev.	Customer
1	2017-07-21	All	Initial registration	000	000	Standard
2						
3						
4						
5						
6						

 Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	2 / 9

1. Features

- ◆ Supports up to 25.78Gbps bit rates
- ◆ Hot-pluggable SFP+ footprint
- ◆ CWDM DFB laser and PIN photodiode, Up to 10km for SMF transmission
- ◆ Compliant with SFP+ MSA and SFF-8472 with duplex LC receptacle
- ◆ Compatible with RoHS
- ◆ Single +3.3V power supply
- ◆ Real Time Digital Diagnostic Monitoring
- ◆ Operating case temperature: 0 to +70 °C
-40 to +85 °C


2. Applications


- ◆ 25GBASE-LR
- ◆ 5G Network
- ◆ Other optical links

3. Description

OEMCx41 is high performance, cost effective modules supporting data rate of 25.78Gbps and 10km transmission distance with SMF. The transceiver consists of three sections: a DFB laser transmitter, a PIN photodiode integrated with a trans-impedance preamplifier (TIA) and MCU control unit. All modules satisfy class I laser safety requirements. The transceivers are compatible with SFP Multi-Source Agreement and SFF-8472 digital diagnostics functions.

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	3 / 9



Transceiver functional diagram

4. Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T _{ST}	-40	+85	°C
Supply Voltage	V _{CC}	-0.5	+4.5	V
Relative Humidity	RH	5	85	%


5. Operation Environment

Parameter	Symbol	Min	Typ	Max	Unit
Date Rate			25.78		Gb/s
Supply Voltage	V _{CC}	+3.14	3.3	+3.47	V
Supply Current	I _{CC}			400	mA
Operating Temperature	T _{OP}	0	25	+70	°C
		-40		+85	°C

6. Optical and Electrical Characteristics (Condition: T_a=T_{OP})

Parameter	Symbol	Min	Type	Max	Unit	Note
Transmitter						
Date Rate			25.78		Gb/s	
Optical Wavelength	λ	$\lambda_c-6.5$	λ_c	$\lambda_c+6.5$	nm	
Average output power	P _O	-7		2	dBm	1
Optical Extinction Ratio	ER	3.5			dB	1
Side Mode Suppression Ratio	SMSR	30			dB	
Data Input Swing Differential	V _N	180		850	mV	2
Input Differential Impedance	Z _N	90	100	110	Ω	
TX Disable	Disable	2.0		V _{CC}	V	

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	4 / 9

TX Fault	Enable		0		0.8	V	
	Fault		2.0		Vcc	V	
	Normal		0		0.8	V	
Receiver							
Date Rate			25.78			Gb/s	
Optical Wavelength	λ	1260		1600		nm	
Receiver Sensitivity				-13.3		dBm	3
Receiver Overload				2		dBm	3
LOS De-Assert	LOS _D			-15		dBm	
LOS Assert	LOS _A	-30				dBm	
LOS Hysteresis		0.5		4		dB	
Data Output Swing Differential	Vout	300		900		mV	4
LOS	High	2.0		Vcc		V	
	Low			0.8		V	


Notes:

- 1). The optical power is launched into SMF.
- 2). PECL input, internally AC-coupled and terminated.
- 3). Measured with a PRBS 231-1 test pattern @25.78Gps, BER $\leq 5 \times 10^{-5}$.
- 4). Internally AC-coupled.

7. Timing and Electrical

Parameter	Symbol	Min	Typical	Max	Unit
Tx Disable Negate Time	t _{on}			2	ms
Tx Disable Assert Time	t _{off}			100	μ s
Time To Initialize, including Reset of Tx Fault	t _{init}			300	ms
Tx Fault Assert Time	t _{fault}			100	μ s
Tx Disable To Reset	t _{reset}	10			μ s
LOS Assert Time	t _{loss_on}			100	μ s
LOS De-assert Time	t _{loss_off}			100	μ s
Serial ID Clock Rate	f _{serial_clock}		100	400	KHz
MOD_DEF (0:2)-High	V _H	2		Vcc	V
MOD_DEF (0:2)-Low	V _L			0.8	V

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL


 Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	5 / 9

8. Diagnostics

Parameter	Range	Unit	Accuracy	Calibration
Temperature	0 to +70	°C	±3°C	Internal
	-40~85			
Voltage	3.0 to 3.6	V	±3%	Internal
Bias Current	0 to 100	mA	±10%	Internal
TX Power	-7 to +2	dBm	±3dB	Internal
RX Power	-14 to +2	dBm	±3dB	Internal

9. Pin Information


Diagram of Host Board Connector Block Pin Numbers and Name



Pin Function Definitions

PIN#	Name	Function	Plug Seq.	Notes
1	VeeT	Transmitter Ground	1	
2	Tx Fault	Transmitter Fault Indication	3	Note 1
3	Tx Disable	Transmitter Disable	3	Note 2
4	SDL	SDA Serial Data Signal	3	
5	SCL	SCL Serial Clock Signal	3	
6	MOD-ABS	Module Absent. Grounded within the module	3	
7	RS0	Not Connected	3	
8	LOS	Loss of Signal	3	Note 3

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	6 / 9

9	RS1	Not Connected	3	
10	VeeR	Receiver ground	1	
11	VeeR	Receiver ground	1	
12	RD-	Inv. Received Data Out	3	Note 4
13	RD+	Received Data Out	3	Note 4
14	VeeR	Receiver ground	1	
15	VccR	Receiver Power Supply	2	
16	VccT	Transmitter Power Supply	2	
17	VeeT	Transmitter Ground	1	
18	TD+	Transmit Data In	3	Note 5
19	TD-	Inv. Transmit Data In	3	Note 5
20	VeeT	Transmitter Ground	1	

Notes:


Plug Seq.: Pin engagement sequence during hot plugging.

- 1) TX Fault is an open collector output, which should be pulled up with a 4.7k~10kΩ resistor on the host board to a voltage between 2.0V and Vcc+0.3V. Logic 0 indicates normal operation; Logic 1 indicates a laser fault of some kind. In the low state, the output will be pulled to less than 0.8V.
- 2) Laser output disabled on TDIS >2.0V or open, enabled on TDIS <0.8V.
- 3) LOS is open collector output. Should be pulled up with 4.7k~10kΩ on host board to a voltage between 2.0V and 3.6V. Logic 0 indicates normal operation; logic 1 indicates loss of signal.
- 4) RD-/+ : These are the differential receiver outputs. They are internally AC-coupled 100 differential lines which should be terminated with 100Ω (differential) at the user SERDES.
- 5) TD-/+ : These are the differential transmitter inputs. They are internally AC-coupled, differential lines with 100Ω differential termination inside the module.

10. Digital Diagnostic Monitor Characteristics

Table 1. Digital Diagnostic Memory Map (Specific Data Field Descriptions)

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 CRE Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	7 / 9




Table 2 - EEPROM Serial ID Memory Contents (A0h)

Data Address	Length (Byte)	Name of Length	Description and Contents
Base ID Fields			
0	1	Identifier	Type of Serial transceiver (03h=SFP28)
1	1	Reserved	Extended identifier of type serial transceiver (04h)
2	1	Connector	Code of optical connector type (07=LC)
3-10	8	Transceiver	
11	1	Encoding	64B/66B (06h)
12	1	BR,Nominal	Nominal baud rate, unit of 100Mbps (67h)
13-14	2	Reserved	(0000h)
15	1	Length(9um)	Link length supported for 9/125um fiber, units of 100m
16	1	Length(50um)	Link length supported for 50/125um fiber, units of 10m
17	1	Length(62.5um)	Link length supported for 62.5/125um fiber, units of 10m
18	1	Length(Copper)	Link length supported for copper, units of meters
19	1	Reserved	
20-35	16	Vendor Name	SFP vendor name: OCRECOM
36	1	Reserved	
37-39	3	Vendor OUI	SFP transceiver vendor OUI ID
40-55	16	Vendor PN	Part Number: "OEMCx41" (ASCII)
56-59	4	Vendor rev	Revision level for part number
60-62	3	Reserved	
63	1	CCID	Least significant byte of sum of data in address 0-62
Extended ID Fields			
64-65	2	Option	Indicates which optical SFP signals are implemented (001Ah = LOS, TX_FAULT, TX_DISABLE all supported)

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL



Communication Limited


Datasheet

DS10-E054
Final Rev.:2017.07.21


Product	SFP+ transceiver OE serials	Ver.	000
Part No.	OEMCX41	Rev.	000
		Page	8 / 9

66	1	BR, max	Upper bit rate margin, units of %
67	1	BR, min	Lower bit rate margin, units of %
68-83	16	Vendor SN	Serial number (ASCII)
84-91	8	Date code	OCRECOM's Manufacturing date code
92	1	Diagnostic type	
93	1	Enhanced option	
94	1	SFF-8472	
95	1	CCEX	Check code for the extended ID Fields (addresses 64 to 94)
Vendor Specific ID Fields			
96-127	32	Readable	OCRECOM specific date, read only
128-255	128	Reserved	Reserved for SFF-8079


11. Recommended Circuit



OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL

 Communication Limited	Datasheet		DS10-E054 Final Rev.:2017.07.21	
	Product	SFP+ transceiver OE serials	Ver.	000
	Part No.	OEMCX41	Rev.	000
			Page	9 / 9

12. Mechanical Dimensions



13. Model Name information

PN	Description
OEMCX41	25G SFP28 SM CWDM 1270nm~1370nm 10KM LC DDMI 0~70 °C
OEMCX42	25G SFP28 SM CWDM 1270nm~1370nm 10KM LC DDMI -40~85 °C

Remark:

C0	C1	C2	C3	C4	C5
1270nm	1290nm	1310nm	1330nm	1350nm	1370nm

OCRE COMMUNICATION LIMITED Web: www.ocrecom.com E-Mail: sales@ocrecom.com Add. Dist.A, Building 6, Bay on the six block, Xixiang, Baoan Dist, Shenzhen, China 518000 Tel: + 86 755 2335 3855 Fax: + 86 755 2335 3855	DESIGN	CHECK	CHECK	APPROVAL